
MATERIAL SPECIFICATION
MS-OR-536 SEALING COMPOUND FOR JOINTS IN CONCRETE AND CONCRETE PIPE

536.1 SCOPE

This specification covers the quality of sealing compound for filling joints in concrete pipe and concrete structures.

536.2 TYPE

The compound shall be a cold-application material unless otherwise specified and shall be a single component or multiple component type.

536.3 QUALITY

The sealing compound shall conform to the requirements of one of the following specifications:

- (a) *ASTM Specification C 990* — Joints for concrete pipe, manholes, and precast box sections using preformed flexible joint sealants.
- (b) *ASTM Specification C 877* — External sealing bands for noncircular concrete sewer, storm drain, and culvert pipe.
- (c) *ASTM Specification D 6690* — Standard Specification for Joint and Crack Sealants, Hot Applied, for Concrete and Asphalt Pavements.
- (d) *ASTM Specification C 920* — Elastomeric joint sealants for cold applied sealing and caulking of joints on mortar and concrete structures not subject to fuel spills. Use type S or M, grade NS for vertical joints; type S or M, grade P or NS for horizontal joints. For class 25, use M, quality materials shall be used for both vertical and horizontal joints unless otherwise specified.

The sealing compound if used with other joint material, such as fillers or gaskets, shall be compatible.